===

Effective Date: September, 2008	**Policy No: UA210.00**
Cross Referenced:	**Origin: Urinalysis**
Reviewed Date: 6/2012	**Authority: Laboratory Director**
Revised Date:01/12	**Page: 1 of 1**

PRINCIPLE: To describe procedure for setup of new instrument, if it is exchanged.

PROCEDURE: As follows.

Service access:

1.   Turn off instrument
2.   When turning instrument on, hold second blue button from left at the same time the instrument is turned on. When sound is heard, let go.
3.   When instrument is in STANDBY, type 2468. This will put the instrument in the service mode.
4.   Type YES for the following prompts:

>   Instrument Test Yes
>   Service   Yes
>   Clear instrument   Yes – will ask 2 x
>   To clear   Yes – will ask 2 x

5.   Turn OFF instrument
6.   Turn ON instrument. You have to check the setup by pressing menu and comparing with the previous setup. It may ask you the sequence of tests. Check with old sequence.
7.   Calibrate.

You also can use this procedure to check the system after maintenance such as lamp replacement, etc. Whatever you want to check, select YES.

INSTRUMENT SET UP

ID   (Time)   (Date)
CT200+   02.09
ENGLISH – CONV
MULTISTIX 10 SG
CT200+ Printer ON
>   Extra Paper Advance OFF
Form Printer OFF
80 Column Printer OFF
Computer ON
>   Handshake ON
>   Checksum ON
>   BAUD Rate: 2400
>   Character Bits: 7
>   Parity: EVEN
Specimen ID Entry ON
Color Entry ON
Clarity Entry ON
Identify Abnormals ON
Display of SEQ # ON
ALTERED RANGES OFF
PLUS System OFF