Section: [Approval: _	3		* PROCE	******** * PROCEDURE * **********************************		6170.038a 1 of 2 July 16, 1990 January 2010
HACKETTSTOWN REGIONAL MEDICAL CENTER Originator: J. Smith, RN Reviewed by: M. Hoffman, RNC Revised by: P. Swanson, RN, MSN NEWBORN SERVICES (Scope) TITLE: NEONATAL CARDIAC-APNEA MONITOR						
PURPOSE:	Te	outli	ne the procedure to monitor t	the neonate's heart rate	e and/or respiration	ns.
EQUIPMENT:	1. 2.		nitor ads			
CONTENT:	PI	ROCE	DURE STEPS:	KI	EY POINTS:	
	1	Pla	ce electrodes on infant's che	st.		
	2	Pla	ce electrodes into connector.	wl	atch colors. Red a nite area lead to w black.	area lead to red; hite; black area lead
	3	Tur	n monitor switch on.		ait 5-10 seconds f nd screen lights to	for bells and chimes come on.
	4	Res	eet limits, if necessary.		onitor has preset l elow).	imits in all areas (see
	5	Mor	nitor baby per physician's ord	lers.		
	6		cument in Cerner under Ongo wborn.	oing Assessment		
	7	Pro	perly charge for equipment a	nd procedure.		
Displays on M	onitor: 1	The	monitor has preset limits in	all areas.		
		a.	ECG lead is set on lead "2."		" is the major lead nd "3" do not trace	for monitoring. "1" as well.
		b.	Filter is "on."		nis takes the artifac nould always be or	
		C.	HR preset limits: 80-180.	Di Pr (u de	splay appears on ress button beside p arrow) or decrea	s, press ECG button. right side of screen. display to increase ase (down arrow) as b button to return to node.
		d.	Respiration rate preset: 30-second apnea period.			ess RESP button. ress button on side

To change limits, press RESP button. Display appears. Press button on side that corresponds with up arrow or down arrow to change rate. Press RESP button to return to regular monitoring

mode.

Index: 6170.038a Page: 2 of 2 Revised Date: January 2010

e. Short-term trends: the machine has been preset for 2 minutes.

Preset 2-minute trend may be gotten by pressing fourth button down one time. Graph shows what the status has been for last 2 minutes. Press the button 3 times to return to normal tracing.

f. Long-term trends: the machine is preset for 1 hour. Push fourth button down twice and graph appears. Shows status of infant for last hour. Press same button 2 more times to return to normal tracing.

2. Memory bank key (trend capability)

To place a picture or tracing in memory, push the "stop" button. The picture is now in memory. Push the "stop" button again to restart the monitor. The next time a tracing is added to the memory bank, the previous tracing is lost.

REFERENCE: <u>Hewlett-Packard 78832A Instruction and Quick Reference.</u>